

CYCLONE® MXi COMMON VENTING KIT

BENEFITS

- Fewer wall penetrations than standard single-unit venting
- Reduced install cost with easy to install non-powered kits
- Flexibility of using PVC or polypropylene vent material

SPECIFICATIONS

- Approved for use with 120, 150, 199, 250, 300, 400 and 500 Cyclone® models
- Approved for side wall (horizontal) vent applications only
- 50 Feet maximum equivalent length of straight pipe common vent and elbows
- Direct vent configuration only
- Maximum of three water heaters can be common vented
- One kit per water heater required, choose from PVC or polypropylene
- Kits include backflow preventer plus intake and exhaust adapters. Piping and termination field supplied.
- Each wall penetration requires a 7" hole through the structure
- Common vent kits are UL listed





COMMON VENT KITS (ONE KIT PER WATER HEATER REQUIRED)

Part Numbers	Description
100227396	PVC Common Vent Kit, 120 – 250 Models
100223775	PVC Common Vent Kit, 300 – 500 Models
100227395	Polypropylene Common Vent Kit, 120 -250 Models
100223774	Polypropylene Common Vent Kit, 300 - 500 Models

Installations must comply with all federal, provincial and local codes.
See kit instructions and corresponding water heater manual for detailed installation instructions and additional information.