



NOTES:

- 1.** THE WORD "WARNING" AND "AVERTISSEMENT" SHALL BE MINIMUM 24 PT. ARIAL BOLD TYPE. PRINT TO BE BLACK ON A SAFETY ORANGE BACKGROUND. WARNING SYMBOL TO BE BLACK TRIANGLE WITH SAFETY ORANGE EXCLAMATION MARK.
- 2.** THIS TEXT TO BE BLACK 14 PT. ARIAL BOLD.
- 3.** THE WORD "WARNING" AND "AVERTISSEMENT" SHALL BE MINIMUM 18 PT. ARIAL BOLD TYPE. PRINT TO BE BLACK ON A SAFETY ORANGE BACKGROUND. WARNING SYMBOL TO BE BLACK TRIANGLE WITH SAFETY ORANGE EXCLAMATION MARK.

- 4.** TEXT IN THIS AREA TO BE BLACK MINIMUM 10 PT. ARIAL REGULAR.
- 5.** LABEL SHALL MEET REQUIREMENTS OF THE LATEST REVISION OF ANSI Z21.10.1.
- 6.** MATERIAL: 4 MIL THICK. U.L. SAFETY STANDARD 969 RECOGNIZED MARKING AND LABELING SYSTEM (PGDQ2) WITH A MINIMUM TEMPERATURE RATING OF 80 DEGREES C. (176 DEGREES F.).
- 7.** LABEL SIZE: 8.40" WIDE X 20.25" TALL.

ANY MATERIAL, COMPONENT, OR VENDOR CHANGE MUST HAVE PRIOR APPROVAL BY THE APPLICABLE PRODUCT ENGINEERING DEPARTMENT.			TOLERANCES UNLESS OTHERWISE NOTED: FRACTIONS ±1/32, DECIMALS (2 PL) ±.03 (3 PL) ±.005, ANGLES ±1°			
ECN	13790-19	NEW DRAWING	Desc:	LABEL.RES.GAS.INFO.WIRING.PV.ENG/FR		
Rev	00		Mat:	SEE NOTE		
Date	02/29/2016		Finish:			
By	RBD	ECR: N/A BASE TEMPLATE: N/A	Drawn:	RBD	Approved:	
			Checked:		Vend Appv:	
			Critical Characteristic For Inspection Purposes:			
			Scale:	1:1	Dwg No:	100262662
			Date:	02/29/2016	Rev:	00