



- NOTES:
1. PRINTING TO BE BLACK ON 3 mil. REMOVABLE INTACT UL 969 MARKING AND LABELING SYSTEM (PGDQ2) WITH A MINIMUM TEMPERATURE RATING OF 80°C.
  2. ONE PIECE LABEL WITH PRINTING IN SPECIFIED SECTIONS AS SHOWN.
  3. MUST BE AGA APPROVED. BACKING MUST HAVE EXTENDED EDGE RELEASE, OR LABELS TO BE IN ROLL FORM.
  4. SAMPLES TO BE SUBMITTED TO A.O.SMITH ENGINEERING DEPARTMENT FOR APPROVAL PRIOR TO PRODUCTION RUN.
  5. PART NUMBER TO APPEAR IN LOWER RIGHT CORNER OF LABEL AS SHOWN.
  6. ALL PRINT TO BE ARIAL REGULAR MINIMIZED BUT LEGIBLE.

Sheet 1 of 1  
 Part Number:  
**330588-000**



ANY MATERIAL, COMPONENT, OR VENDOR CHANGE MUST HAVE PRIOR APPROVAL BY THE APPLICABLE PRODUCT ENGINEERING DEPARTMENT.

TOLERANCES UNLESS OTHERWISE NOTED: FRACTIONS ±1/32, DECIMALS (2 PL) ±.03 (3 PL) ±.005, ANGLES ±1°

ECN	51926-49	RELEASE
Rev	00	
Date	07/10/2014	
By	MRP/YT	

Confidential: This drawing and its information are the exclusive and confidential property of A.O. Smith Corp. and are not to be disclosed, duplicated, distributed, or otherwise used without the written consent of A.O. Smith Corp. All rights reserved. ©

Dwg: LABEL, 1.5 WIRE DIAGRAM		Critical Characteristic For Inspection Purposes:		
Mkt: NOTED				
Drawn: M. PELFREY	Approved:	Scale: 1:1	Dwg No: 330588	Rev: 00
Checked: Y. TENG	Vend Appr:	Date: 07/10/2014		